


Universal Plus basement drain vert., SST, Backw. valve, Waterpr.concr.



Article information

Item no.: 27641
GTIN: 4026092096871
Price group: 10

Description

The polymer Universal Plus basement drain is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket.

The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Type of wastewater:	wastewater without sewage
Installation situation:	floor slab installation

Version:

Emergency closure:	yes
Sealing water height:	60 mm
Backwater protection:	Type 5
Number of mechanical backwater flaps:	2

General characteristics:

Nominal size (DN):	100
Colour:	black
Standard:	EN 1253, EN 13564

Dimensions:

Height:	270 mm
Cutout dimension, length:	310 mm
Cutout dimension, width:	310 mm
Diameter:	295 mm

Tank:

Installation depth:	285 - 340 mm
---------------------	--------------

Drain body:

Socket version:	vertical
Vertical adjustment:	vertically adjustable upper section
Adjustment range:	23 - 80 mm

Coverage features:

Type of cover:	Slotted cover made of stainless steel
Cover material:	304 stainless steel
Colour of cover:	silver
Load class:	K 3 (EN 1253-1)
Length:	200 mm
Width:	200 mm
Height:	25 mm
Sludge bucket:	yes
Discharge rate (l/s) with 10 mm backwater:	1,6 l/s
Discharge rate (l/s) with 20 mm backwater:	1.7 l/s