

## Submersible pump Aquadive KTP 300 with float switch, 10m



### Article information

Item no.: 28840  
GTIN: 4026092000939  
Price group: 20

### Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Type of wastewater: wastewater without sewage

### Version:

Pump control: Float switch

### General characteristics:

Material: Polymer  
Standard: EN 12050-2

### Dimensions:

Length: 275 mm  
Width: 390 mm  
Height: 216 mm

Pressure pipe connection: R 1"  
Free passage: 10 mm

### Pumping device:

Pump: KTP 300  
Number of pumps: 1  
Max. pumping capacity: 8 m<sup>3</sup>/h

Max. pumping height:	6 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S1
Power P1:	0.34 kW
Power P2:	0.21 kW
Speed:	2,800 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Schuko (earthed contact) 2-pin
Weight:	4 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	1.6 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm <sup>2</sup>
Temperature monitoring:	integrated
Insulation class:	F
Cable length:	10 m

**Control:**

Type of level measurement:	mechanical
----------------------------	------------