

## Practicus basement drain DN 100, Black grating, Vertical outlet



### Article information

Item no.: 34102  
GTIN: 4026092047705  
Price group: 10

### Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

### Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

### Version:

Odour trap: no

### General characteristics:

Nominal size (DN): 100  
Outer diameter (OD): 110  
Standard: EN 1253-2

### Dimensions:

Length: 150 mm  
Width: 150 mm  
Cutout dimension, length: 180 mm  
Cutout dimension, width: 180 mm

### Tank:

Number of outlets: 1 ST  
Installation depth: 221 - 277 mm

### Drain body:

Material of drain body: Polymer

Socket version:	vertical
Vertical adjustment:	vertically adjustable upper section

**Coverage features:**

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Sludge bucket:	yes
Locking:	placed

**Grating:**

Rim material:	Polymer
Upper section material:	Polymer
Discharge rate (l/s) with 10 mm backwater:	1,1 l/s
Discharge rate (l/s) with 20 mm backwater:	1.8 l/s