

Parking deck drain, Ecoguss DN 100, round



Article information

Item no.: 48503
GTIN: 4026092036129
Price group: 40

Advantages

- Breakproof & load resistant
- Fulfills highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

Separate equipotential bonding is not necessary.

Version:

System:	100
Waterproofing layer on the drain body:	Connection flange

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-2

Dimensions:

Length:	290 mm
Width:	290 mm
Height:	196 mm
Cutout dimension, length:	300 mm
Cutout dimension, width:	300 mm

Coverage features:

Type of cover:	Round slotted cover
Cover material:	Ecoguss
Colour of cover:	black
Load class:	B 125 (EN 124)
Length:	234 mm
Width:	234 mm
Sludge bucket:	yes
Locking:	Lock & Lift

Grating:

Rim length:	247 mm
Rim width:	247 mm
Rim material:	Ecoguss
Shape of upper section:	round
Upper section material:	Ecoguss
Discharge rate (l/s) with 20 mm backwater:	4.5 l/s