


Ecoguss drain body Press. fl., DN 80, Horizontal outlet



Article information

Item no.: 48783
GTIN: 4026092033388
Price group: 40

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

| | |
|--|---|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the drain body: | Press sealing flange (suitable for creating watertight seals) |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 80 |
| Outer diameter (OD): | 83 |
| Standard: | EN 1253-1 |

Dimensions:

Height: 147 mm
Diameter: 273 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Ecoguss
Socket version: lateral