

Ecoguss drain body Press. fl., DN 100, Vertical outlet



Article information

Item no.: 48811
 GTIN: 4026092032619
 Price group: 40

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

| | |
|----------------------------------------|---------------------------------------------------------------|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the drain body: | Press sealing flange (suitable for creating watertight seals) |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 |
| Standard: | EN 1253-1 |

Dimensions:

| | |
|-----------|--------|
| Height: | 217 mm |
| Diameter: | 273 mm |

Tank:

| | |
|--------------------|------|
| Number of outlets: | 1 ST |
|--------------------|------|

Drain body:

| | |
|-------------------------|----------|
| Material of drain body: | Ecoguss |
| Socket version: | vertical |

| | |
|------------------|-----------------------------------------------------------------------------------------------------|
| Fire protection: | Highest fire protection standards are reached using the optionally available Fire-Kit and Quick-Fit |
|------------------|-----------------------------------------------------------------------------------------------------|