

Linearis Comfort upper section L: 1050 mm, System 125, WaD, K 3



Article information

Item no.: 48931M GTIN: 4026092079072

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Version:

System: 125 Odour trap: included

Type of waterproofing layer: Waterproofing layer

Seepage opening: open

Waterproofing layer on the upper section: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 50 mm

General characteristics:

Nominal size (DN): 125 Outer diameter (OD): 125

Dimensions:

 Width:
 243 mm

 Height:
 115 mm

 null:
 1,115 mm



Coverage features:

Type of cover:
Grating design:
Cover material:
Colour of cover:
Load class:
Stainless steel cover
304 stainless steel
silver, selectable
K 3 (EN 1253-1)
Surface:
Brushed SST
Locking:
Placed

Grating:

Rim length: 1,050 mm Rim width: 66 mm

Rim material: 304 stainless steel

Shape of upper section: square Upper section material: ABS
Discharge rate (l/s) with 10 mm backwater: 1.1 l/s
Discharge rate (l/s) without backwater: 1 l/s