

## Yard drain System 200, horiz., Slotted grating, B 125



### Article information

Item no.: 67923B  
GTIN: 4026092038819  
Price group: 10

### Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius
- Permanently corrosion-free surface

### Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

### Version:

System:	200
Odour trap:	no

### General characteristics:

Nominal size (DN):	100
--------------------	-----

### Tank:

Number of outlets:	1 ST
--------------------	------

### Drain body:

Material of drain body:	Polymer
-------------------------	---------

Socket version:	lateral
Vertical adjustment:	40 - 150 mm

#### Coverage features:

Type of cover:	Round slotted cover
Cover material:	Ecoguss
Colour of cover:	black
Load class:	B 125 (EN 124)
Length:	258 mm
Width:	258 mm
Surface:	EDM
Sludge bucket:	yes
Locking:	Lock & Lift

#### Grating:

Rim length:	258 mm
Rim width:	258 mm
Rim material:	Ecoguss

Shape of upper section:	square
Upper section material:	Ecoguss
Discharge rate (l/s) with 20 mm backwater:	4.5 l/s