

## Pumping station Aquapump Small Duo, Basic, STF 1300



### Article information

Item no.: 828711  
GTIN: 4026092084755  
Price group: 20

### Advantages

- Variable connection options
- With quick-release closures for easy removal and cleaning
- Vertically adjustable upper section

### Description

The pumping station for faecal wastewater is suitable for underground installations and is equipped with a backflow preventer for the pressure pipe. The PE tank is resistant to domestic wastewater and includes a pedestrian class polymer cover plate. The pump with multi-vane impeller ensures maximum operating reliability. Quick-release closures enable the integrated components to be removed easily. The components are pre-assembled for final assembly on site. Including openings for inlet, ventilation and cable duct.

Type of wastewater: wastewater with sewage  
Installation situation: underground installation

### Version:

Type of system: Twin pump station  
Installation: Dry installation  
Pump control: Control unit  
Backflow preventer: integrated

### General characteristics:

Colour: black  
Standard: EN 12050-1

### Dimensions:

Length: 615 mm  
Width: 600 mm  
Height: 830 mm

**Tank:**

Inlet max. scoring (DN):	100 mm
Pumping volume:	60 l
Pressure pipe connection (DN):	50 mm
Pressure pipe connection (OD):	63 mm

**Coverage features:**

Type of cover:	Round cover plate
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Locking:	lockable
Free passage:	40 mm

**Pumping device:**

Pump:	STF 1300
Number of pumps:	2
Max. pumping capacity:	21 m <sup>3</sup> /h
Max. pumping height:	10 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S3 - 50 %
Power P1:	1.3 kW
Power P2:	0.8 kW
Speed:	2,650 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	coded plug
Weight:	10 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	6 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm <sup>2</sup>
Temperature monitoring:	integrated
Insulation class:	F

**Control:**

Control unit:	Basic
Operating voltage:	230 V
Mains frequency:	50 Hz

Self-diagnosis system (SDS):	yes
Battery buffering:	yes
Potential-free contact:	optional
Motor protection switch:	yes
Protection class control unit:	IP 54
Connection type:	Schuko (earthed contact) 2-pin
Length of mains cable for control unit:	1.45 m
Type of level measurement:	mechanical
Level measurement instrument:	Float switch
Alarm sensor:	Float switch