

## Yard drain System 400, DN 100, A, 380 - 510 mm



### Article information

Item no.: 851100A  
GTIN: 4026092004258  
Price group: 10

### Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

### Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals.

The polymer upper section enables continuous height and level adjustment.

### Version:

System:	400
Odour trap:	no

### General characteristics:

Nominal size (DN):	100
Colour:	black
Standard:	EN 752

### Dimensions:

Cutout dimension, length:	585 mm
Cutout dimension, width:	535 mm
Min. insertion depth:	55 mm

### Tank:

Number of outlets:	1 ST
Installation depth:	380 - 510 mm
Groundwater resistant from lower edge of base section:	500 mm

**Drain body:**

Material of drain body:	Polymer
Socket version:	lateral
Vertical adjustment:	vertically adjustable upper section

**Coverage features:**

Type of cover:	Round slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	A 15 (EN 124)
Length:	400 mm
Width:	400 mm
Surface:	EDM
Sludge bucket:	yes

**Grating:**

Rim length:	400 mm
Rim width:	400 mm
Shape of upper section:	square
Discharge rate (l/s) with 20 mm backwater:	4.5 l/s