

Yard drain System 400, DN 100, D, 380 - 510 mm



Article information

Item no.: 851100D
GTIN: 4026092004272
Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals.

The polymer upper section enables continuous height and level adjustment.

Version:

| | |
|-------------|-----|
| System: | 400 |
| Odour trap: | no |

General characteristics:

| | |
|--------------------|--------|
| Nominal size (DN): | 100 |
| Colour: | black |
| Standard: | EN 752 |

Dimensions:

| | |
|---------------------------|--------|
| Cutout dimension, length: | 585 mm |
| Cutout dimension, width: | 535 mm |
| Min. insertion depth: | 55 mm |

Tank:

| | |
|--|--------------|
| Number of outlets: | 1 ST |
| Installation depth: | 380 - 510 mm |
| Groundwater resistant from lower edge of base section: | 500 mm |

Drain body:

| | |
|-------------------------|-------------------------------------|
| Material of drain body: | Polymer |
| Socket version: | lateral |
| Vertical adjustment: | vertically adjustable upper section |

Coverage features:

| | |
|------------------|---------------------|
| Type of cover: | Round slotted cover |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Load class: | D 400 (EN 124) |
| Length: | 450 mm |
| Width: | 450 mm |
| Surface: | EDM |
| Sludge bucket: | yes |

Grating:

| | |
|--|---------|
| Rim length: | 450 mm |
| Rim width: | 450 mm |
| Shape of upper section: | square |
| Discharge rate (l/s) with 20 mm backwater: | 4.5 l/s |