

## Yard drain System 400, DN 150, B, up to 1080 mm



### Article information

Item no.: 851152B  
GTIN: 4026092004418  
Price group: 10

### Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

### Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals.

The polymer upper section enables continuous height and level adjustment.

#### Version:

|                       |          |
|-----------------------|----------|
| System:               | 400      |
| Odour trap:           | included |
| Sealing water height: | 100 mm   |

#### General characteristics:

|                    |        |
|--------------------|--------|
| Nominal size (DN): | 150    |
| Colour:            | black  |
| Standard:          | EN 752 |

#### Dimensions:

|                           |        |
|---------------------------|--------|
| Cutout dimension, length: | 585 mm |
| Cutout dimension, width:  | 535 mm |
| Min. insertion depth:     | 55 mm  |

#### Tank:

|                     |                |
|---------------------|----------------|
| Number of outlets:  | 1 ST           |
| Installation depth: | 730 - 1,080 mm |

Groundwater resistant from lower edge of base section: 500 mm

#### **Drain body:**

Material of drain body: Polymer  
Socket version: lateral

Vertical adjustment: vertically adjustable upper section

#### **Coverage features:**

Type of cover: Round slotted cover  
Cover material: Grey iron  
Colour of cover: black  
Load class: B 125 (EN 124)  
Length: 400 mm  
Width: 400 mm  
Surface: EDM  
Sludge bucket: yes

#### **Grating:**

Rim length: 400 mm  
Rim width: 400 mm

Shape of upper section: square  
Discharge rate (l/s) with 20 mm backwater: 4.5 l/s