

Yard drain System 400, DN 150, D, 730 - 1080 mm



Article information

Item no.: 851152D
GTIN: 4026092004425
Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals.

The polymer upper section enables continuous height and level adjustment.

Version:

System:	400
Odour trap:	included
Sealing water height:	100 mm

General characteristics:

Nominal size (DN):	150
Colour:	black
Standard:	EN 752

Dimensions:

Cutout dimension, length:	585 mm
Cutout dimension, width:	535 mm
Min. insertion depth:	55 mm

Tank:

Number of outlets:	1 ST
Installation depth:	730 - 1,080 mm

Groundwater resistant from lower edge of base section: 500 mm

Drain body:

Material of drain body: Polymer
Socket version: lateral

Vertical adjustment: vertically adjustable upper section

Coverage features:

Type of cover: Round slotted cover
Cover material: Grey iron
Colour of cover: black
Load class: D 400 (EN 124)
Length: 450 mm
Width: 450 mm
Surface: EDM
Sludge bucket: yes

Grating:

Rim length: 450 mm
Rim width: 450 mm

Shape of upper section: square
Discharge rate (l/s) with 20 mm backwater: 4.5 l/s