

## Grease separat. EasyClean Modular free, NS 2, Direct, 3-part



### Article information

Item no.: 93002.00/D1-R2

GTIN: 4026092095720

Price group: 60

### Advantages

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal.

20 year polyethylene warranty.

Installation situation:

free-standing set-up

### Version:

|   |                     |
|---|---------------------|
| Type of disposal:                         | manual              |
| Disposal system:                          | Disposal connection |
| Disposal variant:                         | Direct              |
| Refill inlet in accordance with DIN 1988: | no                  |
| Nominal size (NS):                        | 2                   |
| Inspection window:                        | no                  |
| Shredder-Mix-System:                      | no                  |
| SonicControl:                             | no                  |

Delivery state:

Installation-ready (connection parts must be connected on site)

### General characteristics:

Material: PE  
Standard: EN 1825

### Dimensions:

Set-up area, height: 1,386 mm  
Required access area, length: 1,120 mm  
Required access area, width: 1,020 mm  
Required access area, height: 550 mm  
Height tank bottom up to centre section: 485 mm  
Height centre section: 300 mm  
Height centre section to top edge of tank: 545 mm

### Tank:

Inlet nominal size (DN): 100  
Inlet nominal size (OD): 110 mm  
Outlet nominal size (DN): 100  
Outlet nominal size (OD): 110 mm  
Distance pipe bottom inlet to tank bottom: 1,090 mm  
Distance pipe bottom outlet to tank bottom: 1,020 mm  
Chamber system: three-piece chamber  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: black  
Tightness: odour-tight  
Locking: Quick-release closure

### Wastewater contents:

Separator contents: 270 l  
Total volume: 470 l  
Contents of sludge trap: 200 l  
Storage quantity of grease: 100 l

**Control:**

Control unit: no