

## Grease separator EasyClean free NS 3, Standard, SonicControl



### Article information

Item no.: 93003.02  
 GTIN: 4026092061466  
 Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

### Version:

|   |   |
|---|---|
| Type of disposal:                         | manual with suction hose  |
| Disposal variant:                         | Standard  |
| Refill inlet in accordance with DIN 1988: | no  |
| Nominal size (NS):                        | 3   |
| Inspection window:                        | no  |
| Shredder-Mix-System:                      | no  |
| SonicControl:                             | yes   |
| Load-bearing capacity (DIN 19901):        | F3  |
| Delivery state:                           | Installation-ready (connection parts must be connected on site) |

### General characteristics:

Material: PE

**Dimensions:**

|                               |          |
|-------------------------------|----------|
| Set-up area, length:          | 1,736 mm |
| Set-up area, width:           | 674 mm   |
| Set-up area, height:          | 1,434 mm |
| Required access area, length: | 1,500 mm |
| Required access area, width:  | 674 mm   |
| Required access area, height: | 1,434 mm |

**Tank:**

|   |   |
|---|---|
| Inlet nominal size (DN):                    | 100   |
| Inlet nominal size (OD):                    | 110 mm  |
| Outlet nominal size (DN):                   | 100   |
| Outlet nominal size (OD):                   | 110 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1,055 mm  |
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

**Coverage features:**

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Tightness:       | odour-tight           |
| Locking:         | Quick-release closure |

**Wastewater contents:**

|                             |       |
|-----------------------------|-------|
| Separator contents:         | 300 l |
| Total volume:               | 600 l |
| Contents of sludge trap:    | 300 l |
| Storage quantity of grease: | 120 l |

**Control:**

|               |    |
|---------------|----|
| Control unit: | no |
|---------------|----|