

Grease separator EasyClean free NS 7, Mix, SonicControl



Article information

Item no.: 93007.02/DS
 GTIN: 4026092064948
 Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Simple control
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

The innovative Shredder-Mix-System with integrated macerating system is responsible for homogenising and circulating the tank contents. Cleaning is carried out by an exterior pump which can be disconnected from the tank by a shut-off valve. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. A direct disposal pipe socket is available for odour-neutral manual disposal.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

| | |
|---|------------------------|
| Shut-off valve: | yes |
| Type of disposal: | manual cleaning system |
| Disposal system: | Disposal connection |
| Disposal variant: | Mix |
| Refill inlet in accordance with DIN 1988: | yes |
| Nominal size (NS): | 7 |
| Inspection window: | no |
| Shredder-Mix-System: | yes |
| SonicControl: | yes |
| Water supply: | 1 screw-type valve 1" |
| Load-bearing capacity (DIN 19901): | F3 |

| | |
|--------------------|--|
| Delivery state: | Installation-ready (electrical components, connection parts must be connected on site) |
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection |

General characteristics:

| | |
|-----------|---------|
| Material: | PE |
| Standard: | EN 1825 |

Dimensions:

| | |
|-------------------------------|----------|
| Set-up area, length: | 2,147 mm |
| Set-up area, width: | 1,108 mm |
| Set-up area, height: | 1,892 mm |
| Required access area, length: | 1,910 mm |
| Required access area, width: | 940 mm |
| Required access area, height: | 1,678 mm |

Tank:

| | |
|---|---|
| Inlet nominal size (DN): | 150 |
| Inlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 |
| Outlet nominal size (OD): | 160 mm |
| Distance pipe bottom inlet to tank bottom: | 1,255 mm |
| Distance pipe bottom outlet to tank bottom: | 1,185 mm |
| Pressure pipe connection (DN): | 65 mm |
| Pressure pipe connection (OD): | 75 mm |
| Nominal pressure (PN): | 10 |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Tightness: | odour-tight |
| Locking: | Quick-release closure |

Wastewater contents:

| | |
|--------------------------|---------|
| Separator contents: | 650 l |
| Total volume: | 1,350 l |
| Contents of sludge trap: | 700 l |

Storage quantity of grease: 280 l

Pumping device:

| | |
|--|--|
| Pump: | SPF 300 KE 2.0 |
| Number of pumps: | 1 |
| Max. pumping capacity: | 60 m ³ /h |
| Max. pumping height: | 17 m |
| Operating voltage: | 400 V |
| Mains frequency: | 50 Hz |
| Operating mode: | S2 - 30 min. |
| Power P1: | 3.6 kW |
| Power P2: | 3 kW |
| Speed: | 2,850 U/min |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Connection type: | CEE plug |
| Weight: | 44 kg |
| Impeller type: | Radial impeller with macerating system |
| Length of mains cable for pump: | 5 m |
| Rated current: | 6.2 A |
| Protection class (pump): | IP 55 |
| Protection class: | I |
| Type of pump connection cable: | H07RN-F 7G 1.5 mm ² |
| Temperature monitoring: | integrated |
| Cos phi - power factor: | 0.87 |
| Insulation class: | F |

Control:

| | |
|------------------------------|-------|
| Control unit: | no |
| Type of fuse required (RCD): | 30 mA |