

EasyClean round grease separator free, NS 10, Direct



Article information

Item no.: 93010.05/D

GTIN:

Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Version:

| | |
|---|---|
| Shut-off valve: | yes |
| Type of disposal: | manual |
| Disposal system: | Disposal connection |
| Disposal variant: | Direct |
| Refill inlet in accordance with DIN 1988: | no |
| Nominal size (NS): | 10 |
| Inspection window: | no |
| Shredder-Mix-System: | no |
| SonicControl: | no |
| Load-bearing capacity (DIN 19901): | F3 |
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection |

Dimensions:

| | |
|----------------------|----------|
| Set-up area, length: | 1,900 mm |
|----------------------|----------|

| | |
|-------------------------------|----------|
| Set-up area, width: | 1,690 mm |
| Set-up area, height: | 1,910 mm |
| Required access area, length: | 1,900 mm |
| Required access area, width: | 1,690 mm |
| Required access area, height: | 1,910 mm |

Tank:

| | |
|---|---|
| Inlet nominal size (DN): | 150 |
| Inlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 |
| Outlet nominal size (OD): | 160 mm |
| Distance pipe bottom inlet to tank bottom: | 1,570 mm |
| Distance pipe bottom outlet to tank bottom: | 1,500 mm |
| Pressure pipe connection (DN): | 65 mm |
| Pressure pipe connection (OD): | 75 mm |
| Nominal pressure (PN): | 10 |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Tightness: | odour-tight |
| Locking: | Quick-release closure |

Wastewater contents:

| | |
|-----------------------------|---------|
| Separator contents: | 1,500 l |
| Total volume: | 2,500 l |
| Contents of sludge trap: | 1,000 l |
| Storage quantity of grease: | 400 l |

Control:

| | |
|---------------|----|
| Control unit: | no |
|---------------|----|