

Grease separator EasyClean free NS 10, Direct, Inspection window



Article information

Item no.: 93010.21/D
GTIN: 4026092063613
Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

| | |
|---|---|
| Type of disposal: | manual |
| Disposal system: | Disposal connection |
| Disposal variant: | Direct |
| Refill inlet in accordance with DIN 1988: | no |
| Nominal size (NS): | 10 |
| Inspection window: | yes |
| Shredder-Mix-System: | no |
| SonicControl: | no |
| Load-bearing capacity (DIN 19901): | F3 |
| Delivery state: | Installation-ready (connection parts must be connected on site) |
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection |

General characteristics:

| | |
|-----------|---------|
| Material: | PE |
| Standard: | EN 1825 |

Dimensions:

| | |
|-------------------------------|----------|
| Set-up area, length: | 2,822 mm |
| Set-up area, width: | 973 mm |
| Set-up area, height: | 1,653 mm |
| Required access area, length: | 2,590 mm |
| Required access area, width: | 940 mm |
| Required access area, height: | 1,653 mm |

Tank:

| | |
|---|---|
| Inlet nominal size (DN): | 150 |
| Inlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 |
| Outlet nominal size (OD): | 160 mm |
| Distance pipe bottom inlet to tank bottom: | 1,255 mm |
| Distance pipe bottom outlet to tank bottom: | 1,185 mm |
| Pressure pipe connection (DN): | 65 mm |
| Pressure pipe connection (OD): | 75 mm |
| Nominal pressure (PN): | 10 |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Tightness: | odour-tight |
| Locking: | Quick-release closure |

Wastewater contents:

| | |
|-----------------------------|---------|
| Separator contents: | 900 l |
| Total volume: | 1,900 l |
| Contents of sludge trap: | 1,000 l |
| Storage quantity of grease: | 400 l |

Control:

Control unit:

no