

Grease separator EasyClean free Basic, NS 2, Direct, right, Insp. window



Article information

Item no.: 94002.21DR
GTIN: 4026092083987
Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal:	manual
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	2
Inspection window:	yes
Load-bearing capacity (DIN 19901):	F3

Delivery state: Installation-ready (connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle connection

General characteristics:

Material: PE
Standard: EN 1825

Dimensions:

Set-up area, length: 1,560 mm
Set-up area, width: 815 mm
Set-up area, height: 1,420 mm
Required access area, length: 1,560 mm
Required access area, width: 745 mm
Required access area, height: 1,420 mm

Tank:

Inlet nominal size (DN): 100
Inlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100
Outlet nominal size (OD): 110 mm
Distance pipe bottom inlet to tank bottom: 1,055 mm
Distance pipe bottom outlet to tank bottom: 985 mm
Pressure pipe connection (DN): 65 mm
Pressure pipe connection (OD): 75 mm
Nominal pressure (PN): 10
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover: Cover
Cover material: Polymer
Colour of cover: violet
Tightness: odour-tight
Locking: Quick-release closure

Wastewater contents:

Total volume: 660 l
Contents of sludge trap: 200 l
Storage quantity of grease: 80 l
Max. grease layer thickness: 120 mm