

Grease separator EasyClean free Basic, NS 7, Standard, right, Refill inlet



Article information

Item no.: 94007.12R
 GTIN: 4026092084496
 Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

| | |
|---|---|
| Type of disposal: | manual with suction hose |
| Disposal variant: | Standard |
| Refill inlet in accordance with DIN 1988: | yes |
| Nominal size (NS): | 7 |
| Inspection window: | no |
| Load-bearing capacity (DIN 19901): | F3 |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

General characteristics:

Material: PE

Dimensions:

| | |
|-------------------------------|----------|
| Set-up area, length: | 1,960 mm |
| Set-up area, width: | 1,035 mm |
| Set-up area, height: | 2,000 mm |
| Required access area, length: | 1,960 mm |
| Required access area, width: | 920 mm |
| Required access area, height: | 1,670 mm |

Tank:

| | |
|---|---|
| Inlet nominal size (DN): | 150 |
| Inlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 |
| Outlet nominal size (OD): | 160 mm |
| Distance pipe bottom inlet to tank bottom: | 1,255 mm |
| Distance pipe bottom outlet to tank bottom: | 1,185 mm |
| Pressure pipe connection (DN): | 65 mm |
| Pressure pipe connection (OD): | 75 mm |
| Nominal pressure (PN): | 10 |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features:

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Tightness: | odour-tight |
| Locking: | Quick-release closure |

Wastewater contents:

| | |
|------------------------------|---------|
| Total volume: | 1,370 l |
| Contents of sludge trap: | 700 l |
| Storage quantity of grease: | 280 l |
| Max. grease layer thickness: | 230 mm |