

Grease separator EasyClean free Basic, NS10, Direct, left, wind., Refill



Article information

Item no.: 94010.32DL
 GTIN: 4026092084489
 Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal:	manual
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	yes
Nominal size (NS):	10
Inspection window:	yes
Load-bearing capacity (DIN 19901):	F3
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

General characteristics:

Material: PE
Standard: EN 1825

Dimensions:

Set-up area, length: 2,610 mm
Set-up area, width: 1,120 mm
Set-up area, height: 2,000 mm
Required access area, length: 2,610 mm
Required access area, width: 965 mm
Required access area, height: 1,670 mm

Tank:

Inlet nominal size (DN): 150
Inlet nominal size (OD): 160 mm
Outlet nominal size (DN): 150
Outlet nominal size (OD): 160 mm
Distance pipe bottom inlet to tank bottom: 1,255 mm
Distance pipe bottom outlet to tank bottom: 1,185 mm
Pressure pipe connection (DN): 65 mm
Pressure pipe connection (OD): 75 mm
Nominal pressure (PN): 10
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover: Cover
Cover material: Polymer
Colour of cover: violet
Tightness: odour-tight
Locking: Quick-release closure

Wastewater contents:

Total volume: 1,880 l
Contents of sludge trap: 1,000 l
Storage quantity of grease: 400 l

Max. grease layer thickness: 230 mm