

EasySink sediment separator ground, NS 2, Class D



Article information

Item no.: 97202/00D GTIN: 4026092026915 Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank
- Vertically adjustable upper section with odourtight cover plates with different load classes

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers.

20 year polyethylene warranty.

_						
n	n.	ti	0	n	C	
u	u.	LI	0		3	

Hole diameter of sediment tank: 3, 6, 8, 10, 12, 15 mm Additional price for additional fine screen (mesh size 1.0 mm)

Installation situation: underground installation

\ /		rsi	n
v	м		

Type of disposal: manual with suction hose

Odour trap: included

Nominal size (NS): 2 Load-bearing capacity (DIN 19901): E4

Delivery state: Installation-ready (connection parts must be

connected on site)

General characteristics:

Material: PE



Dimensions:	
Required access area, length: Required access area, width:	1,100 mm 532 mm
Tank:	
Inlet nominal size (DN): Inlet nominal size (OD): Outlet nominal size (DN): Outlet nominal size (OD): Distance pipe bottom inlet to tank bottom: Distance pipe bottom outlet to tank bottom: Installation depth: Groundwater resistant from lower edge of base section: Clear width of entry (LW): Connection inlet/outlet sockets:	100 110 mm 100 110 mm 528 mm 380 mm 55 - 405 mm 500 mm 400 mm PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Vertical adjustment:	vertically adjustable upper section, can be tilted by 5 degrees
Coverage features:	
Type of cover: Cover material: Colour of cover: Load class: Length: Width: Height: Tightness: Locking:	Cover plate Grey iron black D 400 (EN 124) 395 mm 395 mm 52 mm odour-tight and surface water resistant locked
Control:	
Control unit:	no

Volume of collecting tank:

32 l