

Accessories

Pumpfix F, Staufix FKA, Staufix SWA and Controlfix

Extension sections

			Art. no.
with centre flange	<p>Compatibility: For installation in a concrete floor <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Additional function: For installation in water-proof concrete</p> <p>Inclusive: Temporary construction debris cover, fully assembled, gasket set (counter flange made of polymer, screwed, elastomer sealing sheet made of NK/SBR Ø 800 mm)</p> <p>Extension: Max. 360 mm</p>		83 075
with flange and counter flange	<p>Compatibility: For installation in a concrete floor <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Additional function: For connection to an on-site sealing sheet</p> <p>Inclusive: Screws</p> <p>Extension: Max. 140 mm (In case of deeper installation ensure maintenance capability!)</p>		83 073
with gasket	<p>Compatibility: For installation in a concrete floor <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Extension: Max. 180 mm (In case of deeper installation ensure maintenance capability!)</p>		83 070

Cable extensions

for extension from 15 m or 25 m (cable length delivered: 5 m)

	for backwater pumping station <i>Pumpfix F</i>	for motorized backwater valve <i>Staufix FKA and Staufix FKA Standard</i> (up to 2015)		Art. no.
Cable extension for motor (10 m)	<p>Extension to 15 m: 1×80 890</p> <p>Extension to 25 m: 2×80 890</p>	<p>Extension to 15 m: 1×80 890</p> <p>Extension to 25 m: 2×80 890</p>		80 890
Cable extension for probe (10 m)	<p>Extension to 15 m: 2×80 889</p> <p>Extension to 25 m: 4×80 889</p>	<p>Extension to 15 m: 1×80 889</p> <p>Extension to 25 m: 2×80 889</p>		80 889
Cable extension for pump (10 m)	<p>Extension to 15 m: 1×80 891</p> <p>Extension to 25 m: 2×80 891</p>			80 891

Cover plates

		Cover	Art. no.
surface water tight	<p>Compatibility: For installation in a concrete floor <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Inclusive: Gasket</p> <p>Version recessed for on-site tiling, grey: For tile thicknesses of 18 mm (Ventilation always required when in use!)</p>		<p>tileable 830 052</p> <p>black 830 050</p>

Spigot and Socket

		Outer diameter Ø (mm)	Art. no.
Spigot	<p>Compatibility: For backwater valves <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Function: Removable inlets / outlets</p>	Ø 110	83 081
		Ø 125	83 082
		Ø 160	83 083
		Ø 200*	83 084
Socket	<p>Compatibility: For backwater valves <i>Pumpfix F, Staufix FKA, Staufix SWA and Controlfix</i></p> <p>Function: Removable inlets / outlets</p>	Ø 110	83 085
		Ø 125	83 086
		Ø 160	83 087
		Ø 200*	83 088

* In-/Outlet Ø 200, hydraulics corresponds to Ø 160