Backwater valves

Accessories

Pumpfix F, Staufix FKA, Staufix SWA and Controlfix

Hygiene and odd					Art. no
Drain body	Compatibility: For lowest installation; for backwater pumping station <i>Pumpfix F</i>			black grey	680 79 680 79
Drain body	Compatibility: Seal water height 50 mm; for backwater pumping station <i>Pumpfix F</i>	-		black grey	680 79 680 79
additionally <i>Multistop</i>	Compatibility: For backwater pumping station <i>Pumpfix F</i> Function: Odour, foam, rodent and insect stop				48 50
additionally <i>Megastop</i>	Compatibility: For backwater pumping station <i>Pumpfix F</i> Function: Mechanical odour trap inclusive hair filter for KESSEL upper sections		Ø121 14		48 55
additionally odour trap	Compatibility: For backwater pumping station <i>Pumpfix F</i> Seal water height: 50 mm (Ventilation always required when in use!)	1			680 69
Hygiene					Art. no
Hair filter	Compatibility: Art. no. 48 500; for backwater pumping station <i>Pumpfix F</i>		4		48 70
Rodent / Insect for <i>Staufix FKA</i> and S					Art. no
Rat protection flap	Compatibility: <i>Staufix FKA</i> from 01/2011 to 2015 (with flap in pendulum position) Inclusive: Stainless steel shield	Ċ	- 92 - 931 - 931 		80 03
Maintenance					Art. no
Testing funnel	Compatibility: For all <i>Staufix FKA</i> and <i>Staufix SWA</i> backwater valves (Ø 110, Ø 125, Ø 160) Inclusive: Gasket				70 21